

Belt Drive and Blower Applications

Features:

- Class B Ins. (Class "A" see notes)
- Continuous Duty
- Energy Efficient \$ (see notes)
- Open and Enclosed
- Reversible
- Single Speed
- Sleeve & Ball Bearing
- 60 HZ



F678



GK2054

Applications: Centrifugal Pumps, Blowers, Fans

HP	RPM	Volts	Full Load Amps	Service Factor	Frame	Stock Number	Bearings	Protector	Approx. “C”	Dim. “AG”	Enclosure	Notes
1/2	1725	115	8.0	1.25	48/56	GF2054	Sleeve	Auto	9.9	8.3	Open D.P.	92
		115	8.1	1.25	56	GK2054	Sleeve	Auto	10.3	8.3	Open	
		115	7.0	1.25	56	F678	Sleeve	Auto	11.1	9.1	Open D.P.	43
		115	7.0	1.25	56	F505	Ball	Auto	11.1	9.1	Open D.P.	83
		115/208-230	8.2/4.1	1.25	48/56	GF2054D	Sleeve	Auto	9.9	8.3	Open	92
		115/208-230	8.2/4.1	1.25	48/56	BF2054	Ball	Auto	9.9	8.3	Open	92,99
		115	7.0	1.00	56	F352	Ball	Auto	12.6	10.7	TEFC	
		115/230	7.6/3.8	1.00	56	ARS2050D	Sleeve	Auto	10.8	8.8	TEAO	1
		115/230	9.6/4.8	1.25	56	RB2054D	Ball	Auto	10.3	8.3	Open	1,99
		115	6.8	1.00	56	F671	Sleeve	None	11.1	9.1	Open D.P.	
		115	6.8	1.00	56	F675	Sleeve	Auto	11.1	9.1	Open D.P.	43
		115	7.0	1.00	56	F352V1	Ball	Manual	11.1	9.1	TEAO	26
		115	6.8	1.00	56Z	F670A	Ball	Auto	11.1	9.1	Open DP	26,141,260
		115/230	9.6/4.8	1.25	56Z	RB2054DV1	Ball	Auto	10.7	8.3	Open	1,26,307
		115/208-230	7.6/3.8-3.8	1.00	56	ARB2054SL	Ball	None	10.8	8.8	TEAO	26
115/208-230	8.2/4.1	1.25	48Z	BF2054V1	Ball	Auto	10.7	8.3	Open	26,307,341		
	115	6.8	1.00	56Z	F670	Ball	None	11.1	9.1	Open D.P.	295	
	1140	115/230	10.0/5.0	1.25	56	BF2056D	Ball	Auto	11.4	9.5	Open DP	26
3/4	1725	115	12.2	1.25	56	GK2074	Sleeve	Auto	10.8	8.8	Open	
		230/115	5.2/10.4	1.25	56	F681	Sleeve	Auto	11.4	9.5	Open D.P.	
		230/115	5.2/10.4	1.25	56	F680	Ball	Auto	11.4	9.5	Open D.P.	
		115/208-230	11.0/5.4-5.5	1.00	56	F353	Ball	Auto	12.9	10.9	TEFC	
1	1725	115/230	15.6/7.8	1.25	56	GK2104D	Sleeve	Auto	12.3	10.3	Open	

Notes:

- Item to be discontinued when stock is depleted
26. Extended thru bolts, shaft end only
43. Class A insulation
83. Extended thru bolts - 5/8"
92. 48/56 FR = 1/2" x 1.5" Shaft with 5/8" shaft adapter - 48/56 slotted 3" height base
99. 1/2" extended thru bolts, shaft end
141. Shaft diameter is 1/2, N=1.94 with .04 deep flat
260. 56Z = 1/2 flatted shaft
295. 2" shaft length and 1/2" shaft diameter, sleeve and key adapter to 5/8"
307. 1/2" shaft, sleeve and key adapter to 5/8" shaft
341. 1/2" dia. - shaft 2.25" long

