

Single Phase, TEFC**1/3 thru 10 Hp****NEMA 56 thru 215T****Applications:** Wide variety of agri-duty and industrial applications.

Features: Sealed ball bearings, lubricated with high temperature moisture-resistant grease. Drive end seal and v-ring slinger to prevent moisture and contaminant ingress. Condensation drains, gasketed cast conduit boxes. Epoxy paint protects motor from harsh environments.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	“C” Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes ^(a)
Foot Mounted											
1/3	1800	56	FDL3501M	431	K	11.35	23	60	115/230	3	13, 30
1/2	1800	56	FDL3504M	503	K	11.97	28	68	115/230	3.7	12, 30
3/4	1800	56	FDL3507M	591	K	13.35	37	74	115/230	4.4	12
1	1800	56H	FDL3510M	669	K	12.93	41	67	115/230	6.5	30
		143T	FDL3510TM	669	L1	13.29	40	67	115/230	6.5	30
1 1/2	1800	56H	FDL3514M	753	K	13.91	49	80	115/230	6.2	2
		145T	FDL3514TM	755	L1	14.17	51	80	115/208-230	6.2	2
C-Face, Foot Mounted											
1/3	1800	56C	CFDL3501M	578	K	11.35	24	60	115/230	3	13, 30
1/2	1800	56C	CFDL3504M	661	K	11.97	28	68	115/230	3.7	12, 30
3/4	1800	56C	CFDL3507M	768	K	13.35	39	74	115/230	4.4	12
1	1800	56CH	CFDL3510M	867	K	13.25	47	67	115/230	6.5	30
1 1/2	1800	56CH	CFDL3514M	975	K	14.12	51	80	115/208-230	6.2	2
2	1800	56CHZ	CFDL3516TM	1,236	K	14.13	53	82.5	230	7.9	1
C-Face, Footless											
1/3	1800	56C	VFDL3501M	557	K	11.35	23	60	115/230	3	13, 30
1/2	1800	56C	VFDL3504M	638	K	11.97	27	68	115/230	3.7	12, 30
3/4	1800	56C	VFDL3507M	742	K	13.35	44	74	115/230	4.4	12
1	1800	56C	VFDL3510M	840	K	13.25	40	67	115/230	6.5	30
1 1/2	1800	56C	VFDL3514M	951	K	14.12	48	80	115/208-230	6.2	2
Foot Mounted, Extra High Torque											
2	1800	56HZ	FDL3516TM	1,065	K	14.19	51	82.5	230	7.9	1
		182T	FDL3611TM	1,201	L1	16.55	77	75	115/230	14	2
		184	FDL3611M	1,233	L1	15.67	76	74	115/230	12.4	2
3	1800	184	FDL3610M	1,463	L1	17.18	90	80	230	15.5	2, 20
		184T	FDL3610TM	1,428	L1	18.05	90	80	230	15.5	2, 20
		184T	FDL3619TM	1,150	L1	16.54	82	81.5	230	13.2	2, 20
5	1800	184T	FDL3612TM	1,499	L1	18.05	100	80	230	23	2, 20
		215	FDL3731M	1,841	L1	18.65	126	84	230	20.5	2, 20
7 1/2	1800	213	FDL3732M	2,120	L1	18.65	147	84	230	30	2, 20
		213T	FDL3733TM	1,951	L1	19.02	146	84	230	30	2, 20
10	1800	215T	FDL3712TM	2,144	L1	20.77	160	84	230	40	2, 20, 89
		215T	FDL3737TM	2,282	L1	21.27	169	86.5	230	39	2, 20, 89
C-Face, Footless, Extra High Torque											
2	1800	145TC	VFDL3516TM	1,236	L1	14.17	53	82.5	230	7.9	1, 20
3	1800	184TC	VFDL3610TM	1,674	L1	18.05	98	80	230	15.5	2, 20
5	1800	184TC	VFDL3612TM	2,044	L1	18.33	101	80	230	23	2, 20

^(a) See notes on inside back flap.