

F-2 Mount, Three Phase, TEFC and ODP, Foot Mounted



1 thru 100 HpNEMA 143T thru 444T

Applications: Pumps, compressors, fans, conveyors, machine tools and other applications requiring three phase F-2 mounted motors.

Features: Copper windings, ball bearings, heavy-gauge steel frame with base seam-welded. Super-E® motors have NEMA Premium® efficiency and 3 year warranty.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Totally Enclosed Fan Cooled											
1	1800	143T	EFM3546T	706	L1	12.31	35	85.5	208-230/460	1.5	1
1 1/2	1800	145T	EFM3554T	734	L1	13.31	41	86.5	208-230/460	2.2	1
2	1800	145T	EFM3558T	758	L1	13.31	41	86.5	208-230/460	2.9	1
3	3600	182T	EFM3610T	882	L1	15.14	73	86.5	208-230/460	3.6	1
	1800	182T	EFM3611T	841	L1	16.55	73	89.5	208-230/460	4.2	1
5	3600	184T	EFM3613T	978	L1	16.55	91	88.5	230/460	5.9	1
	1800	184T	EFM3615T	920	L1	18.06	91	89.5	208-230/460	6.7	1
7 1/2	3600	213T	EFM3709T	1,465	L1	17.91	128	89.5	208-230/460	9	1
	1800	213T	EFM3710T	1,331	L1	19.01	128	91.7	208-230/460	9.4	1
10	3600	215T	EFM3711T	1,485	L1	17.91	165	90.2	208-230/460	11.8	1
	1800	215T	EFM3714T	1,495	L1	20.51	165	91.7	208-230/460	12	1
15	3600	254T	EFM2394T	2,520	L1	23.16	256	91	230/460	17.5	1,30
	1800	254T	EFM2333T	2,306	L1	23.16	256	92.4	230/460	18.1	1,30
	1200	284T	EFM4100T	3,880	L1	27.76	391	91.7	230/460	21	1,30
20	1800	256T	EFM2334T	2,794	L1	23.16	276	93	230/460	24	1,30
	1200	286T	EFM4102T	5,166	L1	27.76	420	91.7	208-230/460	27	1
25	1800	284T	EFM4103T	3,652	L1	27.76	394	93.6	230/460	30	1,30
30	1800	286T	EFM4104T	4,337	L1	27.76	437	93.6	230/460	36	1,30
40	1800	324T	EFM4110T	5,673	L1	30.28	572	94.1	230/460	48	1,30
	1200	364T	EFM4308T	8,414	L1	33.44	908	94.1	230/460	49.4	1,30
50	3600	326TS	EFM4114T	6,429	L1	28.78	578	93	208-230/460	56	1
	1800	326T	EFM4115T	6,199	L1	30.28	640	94.5	208-230/460	58	1
	1200	365T	EFM4312T	10,167	L1	33.44	902	94.1	230/460	61.7	1,30
60	1800	364T	EFM4314T	8,919	L1	33.44	800	95	230/460	68	30
	1200	404T	EFM4403T	12,341	L1	38.06	1164	95	230/460	69	1,30
75	1800	365T	EFM4316T	10,429	L1	33.44	840	95.4	230/460	84.9	30
	1200	405T	EFM4404T	14,371	L1	38.06	1217	95	230/460	86.9	1,30
100	1800	405T	EFM4400T	12,952	L1	38.31	1160	95.4	230/460	112	
	1200	444T	EFM4409T-4	17,345	L1	44.75	1625	95	460	119	1
Open Drip Proof											
1	1800	145T	EFM3116T	621	L1	11.12	35	85.5	208-230/460	1.5	1
1 1/2	1800	145T	EFM3154T	649	L1	11.62	38	86.5	230/460	2.2	1
2	1800	145T	EFM3157T	696	L1	12.12	40	86.5	230/460	2.9	1
3	1800	182T	EFM3211T	750	L1	15.00	68	89.5	230/460	4.2	1
5	3600	182T	EFM3212T	794	L1	13.62	84	86.5	208-230/460	6	1
	1800	184T	EFM3218T	822	L1	16.50	84	89.5	208-230/460	6.6	1
7 1/2	3600	184T	EFM3219T	1,259	L1	15.00	114	88.5	208-230/460	8.6	1
	1800	213T	EFM3311T	1,207	L1	16.32	114	91	230/460	9.7	1,30
10	3600	213T	EFM3312T	1,440	L1	16.32	125	89.5	208-230/460	12	1
	1800	215T	EFM3313T	1,461	L1	17.45	125	91.7	230/460	12.5	1,30
15	3600	215T	EFM3314T	2,045	L1	16.32	214	90.2	230/460	17.5	1
	1800	254T	EFM2513T	2,069	L1	21.69	214	93	230/460	17.7	1,30
20	1800	256T	EFM2515T	2,597	L1	21.69	226	93	230/460	23.5	1,30
25	1800	284T	EFM2531T	3,166	L1	25.06	313	93.6	230/460	30	1,30
30	1800	286T	EFM2535T	3,462	L1	25.06	339	94.1	230/460	35	1,30
40	1800	324T	EFM2539T	4,516	L1	27.19	392	94.1	230/460	49	1,30
50	1800	326T	EFM2543T	4,983	L1	27.69	547	94.5	230/460	57	1,30
60	1800	364T	EFM2547T	6,274	L1	30.69	622	95	230/460	68	1,30

(a) See notes on inside back flap. Cast Iron Frame Red Catalog Number indicates NEW Product.

General Information

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Large AC Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

HVAC Motors

Farm Duty Motors