

Single Phase, ODP, C-Face

1/6 thru 5 Hp



Features:

- Locked DE bearing to allow mounting in any configuration
- Low noise vibration dampening base
- Dynamically balanced rotor to increase bearing life
- Superior switch design provides optimized torque profiles
- Robust heavy gauge steel design
- Optimized airflow design providing higher horse power in a smaller package

Applications:

- Gear Reducers
- Material Handling
- Machine Tools
- Conveyors
- Pumps
- Fans

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted											
1/3	1800	56C	CEL11301	440	K	10.74	27	72.4	115/230	1.7	15
1/2	3600	56C	CEL11303	458	K	10.74	24	72.4	115/230	2.5	15
	1800	56C	CEL11304	490	K	11.62	32	76.2	115/230	2.4	15
3/4	1800	56C	CEL11307	578	K	12.06	39	81.8	115/230	3.5	15
1	1800	56C	CEL11310	662	K	12.06	44	82.6	115/230	4.2	15
3	1800	184TC	CL1408TM	1012	L1	14.99	80	78	115/230	16	
5	1800	184TC	CL1410TM	1220	L1	16.49	88	82.5	230	23	1, 30
C-Face, Footless, Drip Cover											
1/6	1800	56C	KL1200	299	K	11.22	19	49	115/230	1.9	30
1/4	1800	56C	KEL11203	411	K	11.85	22	68.5	115/230	1.3	15
1/3	3600	56C	KEL11205	432	K	11.85	24	70.5	115/230	1.5	15
		56C	KL1205A	296	K	11.35	21	55	115/230	3	30, 96
		56C	VL1205A	293	K	11.32	23	54	115/230	3.5	
	1800	56C	VEL11301	440	K	11.85	27	72.4	115/230	1.7	15
		56C	VL1301A	352	K	11.32	22	60	115/230	3	30, 96
		56C	VL1303A	337	K	12.00	26	66	115/230	3.7	
1/2	3600	56C	VEL11303	458	K	11.85	24	72.4	115/230	2.5	15
		56C	VL1303A	337	K	12.00	26	66	115/230	3.7	
		56C	VL1304A	420	K	11.57	25	62	115/230	4.2	30, 96
	1800	56C	VEL11304	490	K	12.73	32	76.2	115/230	2.4	15
		56C	VL1304A	420	K	11.57	25	62	115/230	4.2	30, 96
		56C	VEL11305	760	K	13.24	42	76.2	115/230	2.2	15
3/4	3600	56C	VEL11306	478	K	14.04	39	76.2	115/230	3.3	15
		56C	VL1306A	401	K	12.88	30	69	115/230	5.5	
		56C	VEL11307	578	K	13.22	44	81.8	115/230	3.5	15
	1800	56C	VL1307A	548	K	11.75	34	63	115/230	5.4	96
		56C	VEL11308	852	K	14.12	47	80.2	115/230	3.1	15
		56C	VEL11309	556	K	12.06	43	82	115/230	3.9	15
1	3600	56C	VL1309A	423	K	13.40	32	65	115/208-230	7	30
		56C	VEL11318	662	K	13.24	44	82.6	115/230	4.2	15
	1800	56C	VL1318A	581	K	12.75	41	67	115/230	6.2	96
		56C	VEL11313	628	K	14.10	52	82	115/230	5.9	15, 30
1 1/2	3600	56C	VL1313A	578	K	13.01	35	78.5	115/230	6.5	
		56C	VEL11319	783	K	15.50	59	83.8	115/230	6.2	15
	1800	145TC	VL1321T	740	L1	14.17	48	70	115/230	10.5	30
2	3600	56C	VEL11317	691	K	15.47	66	82.9	115/230	7.8	15
		56C	VL1317A	748	K	12.75	44	70	115/230	13	30
	1800	145TC	VL1322T	754	L1	14.18	49	75.5	115/230	10.2	65
3	3600	182TC	VL1406T	916	L1	15.18	61	75.5	115/230	13.6	30, 65
	1800	184TC	VL1408T	927	L1	16.55	78	78	115/230	16	30, 65

(a) See notes on inside back flap.

Red Catalog Number indicates **NEW** Product.