

General Purpose Single Phase Open Dripproof (ODP) Resilient Base, Capacitor Start



APPLICATIONS:

For air compressors, pumps, conveyors, blowers and general industrial equipment.

FEATURES:

- Class A or B Insulation
- Reversible Rotation
- 40°C Ambient
- 60 Hertz
- Continuous Duty

Single Speed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
1/6	900	115	48	3700	\$555	DS-3FMP	1.35	8.9	23	4.5	25
1/4	1800	115/230	48	D14CP2P49	\$326	DS-3FMP	1.35	9.9	16	3.1/1.5	25
	1800	115/230	48	D14CPA2P49	\$341	DS-3FMP	1.35	9.9	18	3.1/1.5	24
	1800	115/230	56	D14CPA2P9	\$333	DS-3FMP	1.35	10.3	14	3.1/1.5	24
	1800	115/230	56	D14CP2P9	\$285	DS-3FMP	1.35	10.3	14	3.1/1.5	25
	1200	115/230	56	D14CPA3P9	\$472	DS-3FMP	1.35	11.8	19	3.70/1.86	24
1/3	3600	115/208-230	48	D13CA1J49	\$281	DS-3FMP	1.35	9.9	21	6/2.9-3.0	24, LA
	3600	115/208-230	56	D13CA1J9	\$281	DS-3FMP	1.35	10.4	19	6/2.9-3.0	24, LA
	3600	115/230	48	D13CPA1P49	\$351	DS-3FMP	1.35	9.9	21	3.7/1.8	24
	1800	115/208-230	56H	D13CA2JH9	\$296	DS-3FMP	1.35	9.8	22	8.8/3.9-4.4	24, LA
	1800	115/230	48	4145	\$277	DS-3FMP	1.00	9.4	22	6.8/3.4	25, LA
	1800	115/230	48	D13CP2P49	\$346	DS-3FMP	1.35	9.9	17	3.8/1.9	25
	1800	115/230	48	D13CPA2P49	\$378	DS-3FMP	1.35	9.9	18	3.8/1.9	24
	1800	115/230	56	D13CPA2P9	\$370	DS-3FMP	1.35	10.3	18	3.8/1.9	24
	1800	115/230 & 110/220	48	6300	\$250	DS-3FMP	1.35	9.4	21	6.5/3.3 & 7.3/3.6	25, 98, LA
	1800	115/230 & 110/220	48	D13CP2Z49	\$312	DS-3FMP	1.35	10.3	18	3.8/1.9	25
	1800	115/230 & 110/220	56	6292	\$303	DS-3FMP	1.35	10.3	22	6.5/3.3	25, 98, LA
	1800	115/208-230	56H	D13CP2PH9	\$378	DS-3FMP	1.35	11.3	17	3.8/1.9	25
	1800	115/208-230	56	D13CPM2PH9	\$374	DS-3FMP	1.34	10.3	16	3.8/1.9	23
	1200	115/208-230	56	D13CA3J9	\$420	DS-3FMP	1.35	11.3	32	6.8/3.4-3.4	24, LA
	1200	115/230	56H	D13CP3PH9	\$507	DS-3FMP	1.35	11.3	26	4.4/2.3	25
	1200	115/230	56H	D13CPA3P9	\$525	DS-3FMP	1.35	11.3	26	4.4/2.3	24
	900	115/230	56	D13CP49	\$816	DS-3FMP	1.35	12.8	39	8.7/4.3	25
1/2	3600	115/230	48	D12CP1P49	\$227	DS-3FMP	1.25	9.9	19	5.0/2.5	25
	3600	115/230	56H	D12CPA1PH9	\$242	DS-3FMP	1.25	11.3	19	5.0/2.5	24
	1800	115/230	48	D12CP2P49	\$283	DS-3FMP	1.25	9.9	22	5.0/2.6	25
	1800	115/230	48	D12CPA2P49	\$330	DS-3FMP	1.25	9.9	14	5.0/2.6	24, 98
	1800	115/230	56H	D12CP2PH9	\$360	DS-3FMP	1.25	11.3	14	5.0/2.6	25
	1800	115/230	56H	D12CPA2PH9	\$378	DS-3FMP	1.25	11.3	15	5.0/2.6	24
	1200	115/230	56H	D12CP3PH9	\$590	DS-3FMP	1.25	12.3	36	4.8/2.4	25
	1200	115/230	56H	D12CPA3PH9	\$685	DS-3FMP	1.25	12.3	36	4.8/2.4	24
3/4	3600	115/208-230	56	D34CA1J9	\$272	DS-3FMP	1.25	11.8	32	10.4/5.3-5.2	24, LA
	3600	115/230	56H	D34CPA1PH9	\$340	DS-3FMP	1.25	11.8	24	7.0/3.6	24
	1800	115/230	56H	D34CP2PH9	\$408	DS-3FMP	1.25	12.3	29	7.0/3.5	25
	1800	115/230	56H	D34CPA2PH9	\$434	DS-3FMP	1.25	12.3	29	7.0/3.5	24
	1800	115/230	56	1660	\$314	DS-3FMP	1.00	10.8	28	11.6/5.8	24
	1200	115/208-230	56H	D34CA3JH9	\$655	DS-3FMP	1.15	13.3	40	10.6/5.4-5.3	24, LA
	1200	115/230	56H	D34CPA3PH9	\$818	DS-3FMP	1.15	13.8	44	6.6/3.4	24
1	3600	115/230	56H	D1CP1PH9	\$475	DS-3FMP	1.25	13.3	29	9.3/4.3	25
	3600	115/230	56H	D1CPA1PH9	\$480	DS-3FMP	1.25	13.3	28	9.3/4.3	24
	1800	115/208-230	56H	D1C2JH9	\$389	DS-3FMP	1.15	12.3	32	14.8/7.5-7.3	25, LA
	1800	115/230	56H	D1CP2PH9	\$486	DS-3FMP	1.15	12.3	32	8.8/4.4	25
	1800	115/230	56H	D1CPA2PH9	\$644	DS-3FMP	1.15	12.3	31	8.8/4.4	24
	1800	115/230	56	D1CPA2P9	\$644	DS-3FMP	1.15	12.3	31	8.8/4.4	24
	1200	115/208-230	56H	D1CA3JH9	\$703	DS-3FMP	1.15	13.8	42	12.6/6.4-6.3	24, LA
	1200	115/230	56H	D1CPA3PH9	\$878	DS-3FMP	1.15	13.1	45	8.9/4.6	24
1 1/2	3600	115/208-230	56	D32CA1JH9	\$510	DS-3FMP	1.15	12.3	28	18.6/9.8-9.3	24, LA
	3600	115/208-230	56H	D32CP1PH9	\$585	DS-3FMP	1.15	13.3	31	13.3/6.7	25
	3600	115/208-230	56H	D32CPA1PH9	\$637	DS-3FMP	1.15	13.3	31	13.3/6.7	24
	1800	115/208-230	145T	D32C2J149	\$566	DS-3SP	1.15	13.7	32	19.2/10.0-9.6	25
	1800	115/230	56H	D32CP2PH9	\$622	DS-3F	1.15	13.3	24	13.4/6.7	25
2	1800	115/230	56H	D32CPA2PH9	\$787	DS-3FMP	1.15	12.3	41	13.4/6.7	24
	3600	115/230	56H	D2CP1PH9	\$665	DS-3FMP	1.15	13.8	41	17.3/8.7	25
	3600	115/208-230	56H	D2CPA1PH9	\$700	DS-3FMP	1.15	13.8	41	17.3/8.7	24
	1800	115/230	56H	D2CP2PH9	\$765	DS-3FMP	1.15	13.5	46	17.0/8.5	25
	1800	115/230	56H	D2CPA2PH9	\$995	DS-3FMP	1.15	13.5	46	17.0/8.5	24

Two Speed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs)	Full Load Amps	Notes
3/4 / 1/4	1800	115	56	6311	\$448	DS-3FMP	1.25	10.8	26	8.9/6.1	25
1 / 1/3	1800	208-230	56	6316	\$501	DS-3FMP	1.15	11.8	32	7.4-7.4/4.0-4.3	25

Note 24 Automatic Reset Thermal Protector Overload

Note 25 Non-protected

Note 98 50/60 Hertz Motor

LA Limited Availability

* All marks shown within this document are properties of their respective owners.

