Single Phase, TEFC

1/3 thru 10 Hp

NEMA 56 thru 215T

Applications: Wide variety of agri-duty and industrial applications.

Features: Sealed ball bearings, lubricated with high temperature moisture-resistant grease. Drive end seal and v-ring slinger to prevent moisture and contaminant ingress. Condensation drains, gasketed cast conduit boxes. Epoxy paint protects motor from harsh environments.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes [a]
Foot Mounted											
1/3	1800	56	**FDL3501M**	431	K	11.35	23	60	115/230	3	13, 30
1/2	1800	56	**FDL3504M**	503	K	11.97	28	68	115/230	3.7	12, 30
3/4	1800	56	**FDL3507M**	591	K	13.35	37	74	115/230	4.4	12
1	1800	56H	**FDL3510M**	669	K	12.93	41	67	115/230	6.5	30
		143T	**FDL3510TM**	669	L1	13.29	40	67	115/230	6.5	30
1 1/2	1800	56H	**FDL3514M**	753	K	13.91	49	80	115/230	6.2	2
		145T	**FDL3514TM**	755	L1	14.17	51	80	115/208-230	6.2	2
C-Face, Foot Mounted											
1/3	1800	56C	**CFDL3501M**	578	K	11.35	24	60	115/230	3	13, 30
1/2	1800	56C	**CFDL3504M**	661	K	11.97	28	68	115/230	3.7	12, 30
3/4	1800	56C	**CFDL3507M**	768	K	13.35	39	74	115/230	4.4	12
1	1800	56CH	**CFDL3510M**	867	K	13.25	47	67	115/230	6.5	30
1 1/2	1800	56CH	**CFDL3514M**	975	K	14.12	51	80	115/208-230	6.2	2
2	1800	56CHZ	**CFDL3516TM**	1,236	K	14.13	53	82.5	230	7.9	1
C-Face, Footless											
1/3	1800	56C	**VFDL3501M**	557	K	11.35	23	60	115/230	3	13, 30
1/2	1800	56C	**VFDL3504M**	638	K	11.97	27	68	115/230	3.7	12, 30
3/4	1800	56C	**VFDL3507M**	742	K	13.35	44	74	115/230	4.4	12
1	1800	56C	**VFDL3510M**	840	K	13.25	40	67	115/230	6.5	30
1 1/2	1800	56C	**VFDL3514M**	951	K	14.12	48	80	115/208-230	6.2	2
Foot Mounted, Extra High Torque											
2	1800	56HZ	**FDL3516TM**	1,065	K	14.19	51	82.5	230	7.9	1
		182T	**FDL3611TM**	1,201	L1	16.55	77	75	115/230	14	2
		184	**FDL3611M**	1,233	L1	15.67	76	74	115/230	12.4	2
3	1800	184	**FDL3610M**	1,463	L1	17.18	90	80	230	15.5	2, 20
		184T	**FDL3610TM**	1,428	L1	18.05	90	80	230	15.5	2, 20
		184T	**FDL3619TM**	1,150	L1	16.54	82	81.5	230	13.2	2, 20
5	1800	184T	**FDL3612TM**	1,499	L1	18.05	100	80	230	23	2, 20
		215	**FDL3731M**	1,841	L1	18.65	126	84	230	20.5	2, 20
7 1/2	1800	213	**FDL3732M**	2,120	L1	18.65	147	84	230	30	2, 20
		213T	**FDL3733TM**	1,951	L1	19.02	146	84	230	30	2, 20
10	1800	215T	**FDL3712TM**	2,144	L1	20.77	160	84	230	40	2, 20, 89
		215T	**FDL3737TM**	2,282	L1	21.27	169	86.5	230	39	2, 20, 89
C-Face, Footless, Extra High Torque											
2	1800	145TC	**VFDL3516TM**	1,236	L1	14.17	53	82.5	230	7.9	1, 20
3	1800	184TC	**VFDL3610TM**	1,674	L1	18.05	98	80	230	15.5	2, 20
5	1800	184TC	**VFDL3612TM**	2,044	L1	18.33	101	80	230	23	2, 20

[a] See notes on inside back flap.