

GILLETTE GENERATORS

LEADER IN BRUSHLESS TECHNOLOGY

MODEL GPE-125EH

60 HERTZ

Heavy Duty, long lasting portable power for contractor and rental use. If you want clean, dependable emergency electric power, with the most reliable engines, then **GEN-PRO** is the right choice for you. These generator sets driven by **EPA Certified** engines are made for the tough jobs when you need the reliability, and good clean emergency. This is exactly what you get, when you choose **GEN-PRO**, because of it's many heavy duty & exclusive features.

| GENERATOR MODEL | GPE-125EH |
|-------------------------|--|
| MAX. KW @ 1 PH. | 12.5 |
| PRIME KW @ 1 PH. | 11.0 |
| PRIME AMPS @ 120 V. | 92 |
| PRIME AMPS @ 240 V. | 46 |
| GENERATOR REGULATION | 5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS. |
| FREQUENCY REGULATION | 5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING |
| "KLEEN-POWER"™ | WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL GEN- PRO GENERATOR SETS |
| ENGINE MODEL (WARRANTY) | HONDA GX630 V-TWIN O.H.V. (3 YEARS) |
| ENGINE START METHOD | 12VDC ELECTRIC ONLY |
| ENGINE HP @ 3600 RPM | 22 HP |
| ENGINE DISPLACEMENT | 2 CYLINDER, 41.97 CU. IN. (688 CC) |
| ENGINE AIR CLEANER | HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS |
| ENGINE FUEL TANK | 7 GAL. (26.5 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE |
| ENGINE OIL SYSTEM | FULL PRESSURE W/ SPIN ON OIL FILTER |
| LOW OIL PROTECTION | AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL |
| db(A) AT 7 METERS | 86 |
| 3/4 LOAD RUN TIME (HRS) | 5.4 |
| FUEL USE, GAL/LTR/HR | 1.3 / 4.92 |
| MOTOR START POWER | 5 HP, CODE G ELECTRIC MOTOR |
| CRANE PICK-UP HOOK | OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET |
| 2-WHEEL DOLLY KIT | OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND "NEVER GO FLAT" WHEELS |
| MAINLINE CB | ◆EXCLUSIVE: GFCI PLUS OVERLOAD CIRCUIT BREAKER PROTECTION |
| HOUR METER | HOUR METER WITH (3) MAINTENANCE ALERTS |
| POWER RECEPTACLES | (4) NEMA 5-15R, (1) L5-30R 120 VOLTS, AND (1) 14-50R 240 VOLTS RECEPTACLES |
| PROTECTIVE ROLL FRAME | RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE GEN-SET |
| LENGTH, INCHES | 38 |
| WIDTH, INCHES | 26 |
| HEIGHT, INCHES | 28 |
| SHIP WEIGHT, LBS. | 325 |
| CU. FEET SHIP BOX | 20 |

♦ GFCI, GROUND FAULT CIRCUIT INTERRUPTER ON ALL 120 AND 240 VOLT RECEPTACLES.

SPC1-GPE-125EH-20120601

GILLETTE GENERATORS, INC. 1340 WADE DRIVE ELKHART, IN 46514 USA TEL. (574) 264 - 9639 WEB-SITE: http://www.gillettegenerators.com E-mail: sales@gillettegenerators.com FAX (574) 262 - 1840