

Built for a lifetime."

Portable Compressors

Mobilair™ M64



Versatile

The Mobilair™ M64 is a versatile portable rotary screw compressor suitable for all outdoor applications including sand blasting, pavement breaking and general air tool use, as well as portable backup for stationary compressors. It produces 225 cfm at 100 psig and other pressures are available.

The M64 offers has many features that make it very user-friendly. Units come standard with an easy-to-read control panel including a push-to-load switch. The large fuel tank provides

extended operation and has a large filler neck with overflow protection for safe, easy filling. A torsion bar suspension system and oversized tires provide superior road handling. The canopy is also super-soundproofed and provides extremely low decibel levels – just 70 db(A) at 23 feet.

Efficient and Reliable

A heavy-duty 4-cylinder engine combined with our energy saving Sigma Profile airend produces more air with less horsepower. To eliminate tool freeze up, another standard feature is

Standard Features:

- Sigma Profile rotary screw airend with direct drive produces more air with less horsepower
- Heavy-duty 4-cylinder diesel engine complies with current Tier 4 EPA emissions standards
- · Large fuel tank for extended operation
- High capacity cold start battery ensures reliable operation even under extreme working conditions
- Proprietary anti-frost thermostatic valve avoids tool freeze-ups
- Weatherproof toolbox

Optional Features:

- Pressures to 145 psig
- · Five year airend warranty
- Aftercooler and filtration packages
- · 8 kVA generator

our proprietary anti-frost thermostatic valve. The M64's heavy-duty steel chassis and powder-coated canopy stand up to the harshest conditions. Both the canopy and solid steel flooring protect the motor, airend, and critical components from dirt, water, and other contaminants. The engine and compressor inlets are filtered. This protection, combined with a high efficiency cooling system allows the M64 to operate in ambient temperatures up to 122°F.

1() Outstanding Advantages



8 kVA Generator option

- Easy access with gull-wing doors
- Easy to read instrument panel with load switch
- 1 micron compressor air inlet filter with maintenance indicator protects the equipment
- 4 Direct drive Sigma Profile airend produces more air with less fuel consumption
- Heavy-duty diesel engine complies with Tier 4 emissions standards
- 10 micron spin-on oil filter with integral anti-frost thermostatic valve
- Heavy-duty bumpers and lighting kit are standard
- Extra-large capacity fuel tank provides 9 hours of operation
- Thick sound proofing for super low noise level
- Convenient weatherproof tool box (not shown)

Specifications

Compressor		Diesel Engine		Package		Dimensions (in.)	
Free air delivery	225 cfm	Make	Kubota V2403T	Fuel tank capacity	28 gal.	Length*	144
Working Pressure	100 psig	Power at full load	49.6 hp	Weight, dry	2512 lb.	Width	68
		Full load speed	2700 rpm	Outlets	2 x ¾"; 1 x 1"	Height	56
		Off load running speed	2000 rpm	Sound level max	76 db(A) at 23 ft.	*includes tow bar	

Specifications are subject to change without notice.



www.kaeser.com

Built for a lifetime."

Kaeser Compressors, Inc.

511 Sigma Drive Fredericksburg, VA 22408 USA Telephone: 540-898-5500 Toll Free: 800-777-7873 info.usa@kaeser.com







Kaeser Compressors Canada Inc.

3760 La Verendrye Street Boisbriand, QC J7H 1R5 CANADA Telephone: (450) 971-1414 Toll free: (800) 477-1416 info.canada@kaeser.com

Kaeser Compresores de México S de RL de CV

Calle 2 #123 Parque Industrial Juríca 76100 Querétaro, Qro. Telephone: 01 (442) 218 64 48 sales.mexico@kaeser.com

Kaeser Compresores de Guatemala y Cia. Ltda.

Calzada Atanasio Tzul 21-00, Zona 12, Complejo Empresarial El Cortijo II, Bodega 501 01012 Guatemala Telephone: +502 2412-6000

info.guatemala@kaeser.com