

ITT

BCPT

Residential Water Systems

CentriPro

T Series

Epoxy Coated Diaphragm Tanks




Stand Model
(Vertical)



In-Line Pipe Mounted
Model

FEATURES

- **Deep Drawn Steel Shells:** provide maximum material strength.
- **Inner Shell:** Prevents diaphragm from over-expanding.
- **Heavy Duty Diaphragm:** Made of finest quality butyl rubber. Separates air and water, maintains air change.
- **Interior Tank Lining:** Tank features a durable fusion bonded polymeric lining. Meets FDA requirements.
- **Maximum Working Pressure:** 100 PSI.
- **Temperature Rating:** Maximum 120° F.
- **Epoxy Coated System Connection:** On all stand and in-line models.
- **Appliance Appearance Exterior Finish:** Tan color, high durability exterior finish of tough, powder coat over a zinc phosphate surface treatment.
- Tanks are designed for installation indoors or where they are protected from rain, irrigation overspray, salt air and other corrosive environments. Always protect tanks from freezing.
- **Heavy Duty High Density Polypropylene Base:** Eliminates corrosion due to condensation and exposure to the elements.
- **Tanks have a 5-year limited warranty. See instruction manual for complete warranty details.**



CentriPro®

CentriPro is a brand of ITT Corporation.

www.centripro.com

Engineered for life



Certified to ANSI/NSF 61

	Model No.	Total Volume (Gals.)	Drawdown in Gallons at System Operating Pressure Range of			Maximum Drawdown Vol. (Gals.)	Pre-Charge PSI	System Connection	Dimensions		Shipping Weight	Height From Floor to Center of Base Opening
			20/40 PSIG	30/50 PSIG	40/60 PSIG				Diameter	Height		
Stand Models	T45	13.9	5.1	4.3	3.7	8.4	38	1" NPTF	15 ³ / ₈	24 ¹⁵ / ₁₆	24	3 ¹ / ₈
	T60	19.9	7.3	6.1	5.3	12.1	38	1" NPTF	15 ³ / ₈	32 ³ / ₈	34	
	T80	25.9	8.9	7.7	6.7	13.9	38	1" NPTF	15 ³ / ₈	39 ³ / ₁₆	43	
	T100	31.8	11.8	9.9	8.6	13.8	38	1" NPTF	15 ³ / ₈	47 ¹ / ₄	52	
	T140	45.2	16.5	13.9	12.1	27.3	38	1 ¹ / ₄ " NPTF	22	36 ³ / ₁₆	64	3 ³ / ₈
	T200	65.1	23.9	20.0	17.4	39.3	38	1 ¹ / ₄ " NPTF	22	48 ⁵ / ₈	89	
	T250	83.5	30.9	25.9	22.5	50.8	38	1 ¹ / ₄ " NPTF	26	46	116	3 ¹ / ₂
	T260	84.9	31.2	26.2	22.8	44.7	38	1 ¹ / ₄ " NPTF	22	60 ¹ / ₁₆	113	3 ³ / ₈
	T350	115.9	42.9	35.9	31.3	70.5	38	1 ¹ / ₄ " NPTF	26	61 ⁵ / ₁₆	161	3 ¹ / ₂
In-Line Models	T15P	4.5	1.7	1.4	1.2	2.7	38	3/4" NPTM	11	13 ¹⁵ / ₁₆	12	
	T25P	8.2	3.1	2.6	2.2	4.5	38	3/4" NPTM	11	23 ¹ / ₁₆	21	
	T45P	13.9	5.1	4.3	3.7	8.4	38	1" NPTM	15 ³ / ₈	21 ¹ / ₁₆	24	

NOTES:

P = Pipe Connection

(All dimensions are in inches and weight in lbs. Do not use for construction purposes.)

ACCESSORIES



AW39T Bracket:
Universal pump mounting bracket for use on all tan stand model tanks.

Order No.	Description	Wt. (lbs.)
AW39T	Universal Jet Pump Bracket - Tan	2



ITT
2881 East Bayard Street, Seneca Falls, NY 13148
Phone: (315) 568-7123 • Fax: (315) 568-7973
www.centripro.com

CentriPro is a registered trademark of ITT Corporation. ITT, the Engineered Blocks Symbol and Engineered for Life are registered trademarks of ITT Manufacturing Enterprises, Inc.

Copyright © 2009 ITT Corporation BCPT July, 2009 Printed in U.S.A.
SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

